

TYPE RSB TABLEAU DE DIMENSIONS ET PUISSANCES

TYPE O DIMENSION AND CAPACITY TABLE

Ø	tolérances Tolerance	diamètre de la tête Connection head Ø	raccordement Connection
32,0 mm	± 1,00	38 mm	M5 borne / strand
36,0 mm	± 1,50	45 mm	M5/M6 borne / strand
46,0 mm	± 2,00	54 mm	M5 borne / strand
58,0 mm	± 2,00	70 mm	M6 borne / strand

Ø	W/cm ²	longueur / length							
		250	300	400	500	600	800	1000	1250
32,0 mm	1,2			425 W	550 W	650 W	900 W	1150 W	1400 W
	4,0	800 W	1000 W	1400 W	1600 W	2000 W	3000 W	3800 W	4600 W
36,0 mm	1,2			475 W	625 W	750 W	1000 W	1300 W	1600 W
	4,0	900 W	1150 W	1600 W	2000 W	2500 W	3500 W	4400 W	5550 W
46,0 mm	1,2		450 W	625 W	800 W	1000 W	1325 W	1700 W	2000 W
	4,0	1200 W	1500 W	2000 W	2600 W	3200 W	4500 W	5600 W	6800 W
58,0 mm	1,2		550 W	750 W	1000 W	1200 W	1600 W	2000 W	2500 W
	4,0	1500 W	1800 W	2500 W	3300 W	4000 W	5500 W	7000 W	8500 W

sous réserve de modifications techniques / Subject to prior sale and technical change
autres dimensions possibles / other dimensions possible

Schéma type RSB / Type O sketch

